# **Working Light**

## Working Light for downdraft table



## Description

Working Light, to be mounted to the back panel or backdraft panel of a downdraft table. The cable is to be connected at the rear. The cover can be hinged to facilitate exchange of the fluorescent light.

The working light is activated upon turning on the main switch of the downdraft table.

#### **Specifications**

Physical dimensions and properties	
Dimensions cover:	
- length	- 1325 mm (52.17 in.)
- height	- 111,5 mm (4.39 in.)
- depth	- 153 mm (6.02 in.)
Material	sheet metal
Colour	yellow RAL 1028 (gloss grade 85%)
Weight (net)	6,5 kg (14.3 lbs)
Connection cable	2,3 m (7.5 ft)
<ul> <li>Electrical data</li> </ul>	
Lamp type	fluorescent light T8
Lamp size:	
- length	- 650 mm (25.6 in.)
- diameter	- Ø 50,8 mm (2 in.)
Power consumption	18 W
Connection voltage	230V/1~/50Hz
Protection class	IP 65
Plug type	IEC
Product combinations	
DNF	downdraft table to be connected to external extraction and filtration facility
DFD	downdraft table with disposable filter (with back panel or backdraft kit)

DFS	downdraft table with manual self- cleaning filter (with back panel or backdraft kit)
DFS/A	downdraft table with automatic self- cleaning filter (with back panel or backdraft kit)
<ul> <li>Scope of supply</li> </ul>	
Covered light fixture with fluc cable - Bolt M6 (6) - Tie-wrap	prescent light and 2,3 m (7.5 ft) of (3)
Order information	
Article number	0040300010
Number/package	1
<ul> <li>Shipping data</li> </ul>	
Gross weight	7,5 kg (16.5 lbs)
Packing dimensions	1330 x 155 x 170 mm (52.4 x 6.1 x 6.7 in.)
Harmonized Tariff Code	84213920
Country of origin	Sweden
Approvals/certificates	
CE	
RoHS 2002/95/EC	

### Features



Product type Art. no. Product category : options and accessories

Version

: 170408/0

: Working Light

: 0040300010

Euromate BV P.O. Box 9350 1800 GJ Alkmaar The Netherlands www.euromate.com



**PRODUCT DATA SHEET**